

REINIGER Alkaline cleaning agent for mixing trucks and construction machines

Item No 1181

FIELDS OF APPLICATION

REINIGER is a liquid agent for cleaning mixing vehicles and construction machines. REINIGER is especially suitable for undertaking the washing process with high pressure cleaners or in car wash facilities.

WORKING PRINCIPLE

REINIGER removes dirt containing grease, mineral oil and eliminates heavy layers of dirt from mixing vehicles and construction machines

TECHNICAL DATA

Homogeneity	homogenous
Colour	yellowish
Chemical base	surfactants
State	liquid
Density	1.08 ± 0.03 g/cm ³
Workability	from +1 °C
Shelf life	approx. 1 year from date of production if stored properly
Storage conditions	Store in unopened, original sealed packag- ing between +5 °C and +25 °C. Protect from frost and insolation.

APPLICATION QUANTITY

The application quantity depends on the surface structure, its absorbency and its contamination level and needs to be determined in each individual case.



PROCESSING INDICATIONS

REINIGER should be diluted with water before using. The concentration can be chosen according to the degree of soiling. The surface resistance should be tested in advance. The application is done with a spraying appliance, a brush or a broom. **Do not allow drying!** Thoroughly rinse the cleaned surfaces with clean water.

For a washing process with high pressure cleaners Recommended dilution ratio: 1:3

For a washing process with spaying appliances or manual washing Recommended dilution ratio: 1:19

This product is classified as hazardous according to the CLP regulations. See safety data sheet for further information.

REMARKS

This information describes the application- and processing possibilities of a product and its operation principles under regular conditions. Having no influence on the further application and processing, especially in conjunction with other construction materials, the given indication are neither a warranty in respect of the product's properties or its fitness for a particular purpose nor a full instruction of use. This information, any other recommendation or verbal advice are not binding and do not infer to any liability or legal demand.

Due to continuous further development, the most recent Technical Data Sheet is valid and will be supplied on request. All orders are accepted subject to our current general terms and conditions.

Edition: 16th March 2017

PACKAGING

- 301 can
- 200 l barrel
- 1000 l container

SUITABILITY- AND PRE-TESTS ARE NECESSARY BEFORE APPLYING THE CONCRETE ADMIXTURE!