

HYGROSMART® FLOOR-H

Hardener for Industrial Floor Surfaces

DESCRIPTION

HYGROSMART® FLOOR-H is a high strength mortar based on cement and quartz aggregates and reinforced with special modified polymers which make it suitable for hardening the surface of industrial flooring.

COMPLIANCE-CERTIFICATION

Exceeds requirements of **EN 13813** standard.

RECOMMENDED FOR

Suitable for high performance heavy duty flooring such as industrial floors, basements, parking spaces, warehouses, loading-unloading spaces etc.

APPLICATION PROCEDURE

The product is applied dry, in two layers, with broadcasting on the floor concrete as soon as it starts setting. The floor treatment and the hardener incorporation is done with special grinding machinery.

CONSUMPTION

3-5 Kg/m².

CLEANING

Brushes and tools can be cleaned with water. Dried product cannot be cleaned with water and can be removed only by mechanical means.

PACKAGING

25Kg paper bags

Color: grey

STORAGE

The product can be kept for minimum 12 months in the original unopened packaging. Should be stored in dry conditions and at temperatures of 5-25°C. Once opened, use as soon as possible.

SAFETY

HYGROSMART®-ADHESIVE TH contains cement and is therefore irritating. Please use protective equipment and clothing during application.

HYGROSMART® FLOOR-H

TECHNICAL SPECIFICATIONS

PROPERTY	UNIT	RESULT
Density of dry mix	kg/l	1,6
Compression	N/mm ²	72,00±2,00
Bending	N/mm ²	8,00±1,00

NONE OF OUR PUBLISHED INSTRUCTIONS AND SPECIFICATIONS, IN WRITING OR OTHERWISE, ARE BINDING EITHER IN GENERAL OR WITH RESPECT TO ANY THIRD PARTY RIGHTS, OR DO THEY RELIEVE INTERESTED PARTIES OF THEIR DUTY TO SUBJECT THE PRODUCT TO AN ADEQUATE EXAMINATION OF ITS SUITABILITY. IN NO EVENT WILL ALCHIMICA S.A. BE RESPONSIBLE FOR DAMAGES OF ANY NATURE, WHATSOEVER, RESULTING FROM THE USE OF OR RELIANCE UPON INFORMATION OR THE PRODUCT TO WHICH INFORMATION REFERS.

